



Transportation Plan for CKL-1000i

Boom Spec : CR 48.8 mts. + No Jib

Boom Spec. (CR 48.8 m + No jib)	
Main	Jib
10ft - 2	10ft - 0
20ft - 1	20ft - 0
40ft - 2	

Sl.No.	Trailer	Description	Qty	Wt. (Tons)	Total Wt.	LXWXH (In meter)	Lashing Requirements
1	Low Bed	1. Main body with Lower Boom & Back Stop	1	46.13	46.33	12.190X3.5X3.15	Chain - 2nos Belt - 2 nos
		2. Tool Box	1	0.2			
2	High Bed	1. C/W No.E (12 T)	1	12.48		12.2X2.5X1.5	Chain - 4 nos Belt -4 nos
		2. C/W No.B (7T)	1	7.38			
		3. 40 ft boom AB	1	0.975	20.835		
3	High Bed	1. C/W No.D (9T)	1	9.36		12.2X2.5X1.5	Chain - 4 nos Belt -6 nos
		2. Guy Cable Box	1	0.5			
		3. Carbody C/W	2	7.3	17.16		
4	High Bed	1. 40ft Boom insert	1	0.96		12.2X3.1X2.7	Chain -not required Belt -8 nos
		2. 10ft +10ft + 20ft Boom insert	1	1.14	2.1		
5	High Bed	1. Aux. Sheave	1	0.195		12.2X2.5X1.5	
		2. 35 T hook	1	0.7			
		3. 11 T Ball hook	1	0.3			Chain -not required Belt -8 nos
		4. Adapter - 4 nos.	1	0.08			
		5. 70 T hook	1	1.73			
		6. Upper Boom	1	1.17	4.175		

17

90.6